



DRUM SCREEN 1020

TECHNICAL DATA

TRAILER DRUM SCREEN

| | | | |
|------------------|-----|---|-------|
| - Dimension Drum | mm. | - | κ1000 |
| Screen net | mm. | | 5-100 |

FEEDING: BELT WITH HOPPER

| | | | |
|-------------------|----------------|---------|------|
| - Length | mm. | - Width | 2500 |
| | mm. | | 550 |
| - Hopper capacity | m ³ | | 1.3 |
| - Loading Height | mm | | 2000 |

FINE MATERIAL BELT

| | | | |
|----------|-----|---------------|------|
| - Length | mm. | - Width | 2500 |
| | mm. | - Pile height | 500 |
| | | | 1270 |

OVERSIZE MATERIAL BELT

| | | | |
|----------|-----|---------------|------|
| - Length | mm. | - Width | 1800 |
| | mm. | - Pile height | 500 |
| | | | 1585 |

GENERATORE DI CORRENTE

| | | |
|------------------|-----|-----------|
| Corrente erogata | kVa | 14 |
| | kV | 9 |
| | V | 380 - 220 |

MOTORE ISUZU

| | | |
|------------------|-------|---------|
| - Potenza | kW/Hp | 21\28,5 |
| - Consumi | L/h | 5,5 |
| - Cilindri | N° | 3 |
| - Raffreddamento | | acqua |

TANDEM AXLES

| | | |
|--------------|------|---------|
| -Type | | Tridem |
| -Towbar type | | Caravan |
| -Max speed | Km/h | 80 |

*PERFORMANCE

| | | |
|-------------------|-----|------|
| - Production | T/h | 60 |
| - Max size | mm. | 20 |
| - Standard weight | Kg. | 3400 |

STANDARD MACHINE

- Assale per la circolazione stradale
- Brushes for clean drum
- Belts for the screening material

ACCESSORIES

- Rubber Crawled Track (Version)
- Remote Control(Only Crawl)
- Net With Different Hole
- Dust Dumping System

DIMENSION At Work Transport

| | | | |
|------------|-----|------|------|
| -Lunghezza | mm. | 6500 | 6500 |
| -Larghezza | mm. | 5850 | 2500 |
| -Altezza | mm. | 2460 | 2460 |

**The screen production performance depends by the type of material.*

