



DRUM SCREEN TRACK 1020

TECHNICAL DATA

TRACKED DRUM SCREEN

| | | |
|------------------|-------|-------|
| - Dimension Drum | mm. - | κ1000 |
| Screen net | mm. | 5-100 |

FEEDING: BELT WITH HOPPER

| | | |
|-------------------|----------------|------|
| - Length | mm. - Width | 2500 |
| | mm. | 550 |
| - Hopper capacity | m ³ | 1.3 |
| - Loading Height | mm | 2000 |

FINE MATERIAL BELT

| | | |
|----------|-------------------|------|
| - Length | mm. - Width | 2500 |
| | mm. - Pile height | 500 |
| | mm. | 1270 |

OVERSIZE MATERIAL BELT

| | | |
|----------|-------------------|------|
| - Length | mm. - Width | 1800 |
| | mm. - Pile height | 500 |
| | mm. | 1585 |

INSIDE GENERATOR

| | | |
|----------------|-----|----------|
| Electric power | kVa | 14 |
| | kV | 9 |
| | V | 380- 220 |

MOTORE ISUZU

| | | |
|---------------|-------|---------|
| - Power | kW/Hp | 21\28,5 |
| - Consumption | L/h | 5,5 |
| - Cilynder | N° | 3 |
| - Cooling | water | |

RUBBER CRAWLED TRACK

| | | |
|----------|-----|----------|
| -Length | mm. | 2000 |
| -Width | mm. | 300 |
| -2°speed | | INCLUDED |

*PERFORMANCE

| | | |
|-------------------|-----|------|
| - Production | T/h | 60 |
| - Max size | mm. | 20 |
| - Standard weight | Kg. | 3400 |

STANDARD MACHINE

- Brushes for clean drum
- Belts for the screening material

ACCESSORIES

- Net With Different Hole
- Dust Dumping System

DIMENSION At Work Transport

| | | | |
|---------|-----|------|------|
| -Length | mm. | 5500 | 5500 |
| -Width | mm. | 5800 | 2150 |
| -Height | mm. | 2300 | 2150 |

**The screen production performance depends by the type of material.*



The technical data and specification hereby supplied are merely indicatives. Komplet reserves the right to modify them without notice