



from 180 to 300 HP Ø50 cm max (stones) D25 cm

**STONE CRUSHER FOR TRACTORS WITH FIXED TEETH ROTOR.**

The STCH is designed for the toughest applications. With multiple working widths available, it can crush stones up to 50 cm diameter. The largest model, STCH-250, allows you to reclaim unprocessed land containing stones. The Heavy Duty (HD) version of the STCH has upgraded teeth and additional layers of Hardox® steel to ensure a longer working life for this attachment.

STANDARD EQUIPMENT		
PTO shaft (STCH/HD)	Penetration skids	
Cam clutch on side PTO (STCH/HD)	Adjustable extended 3 point linkage (STCH/HD)	
PTO shaft with cam clutch (STCH)	Enclosed machine body	
Gearbox with freewheel	Inside lateral protection	
Trasmission with belts in XPC	Dual row protection chains	
Hydraulic hood		
Flat pressed welded steel counter-blades	OPTIONS	
Adjustable Hardox® counter-blade	Hydraulic top link	
Inner anti wear clad plates FCP (STCH/HD)	Dozing blade	
Adjustable skids	Grader blade	
	Multiple tooth options (STCH/HD: STC/3/HD tools standard)	



**FEATURES**

- Enclosed machine body** protects internal components
- Hydraulically controlled hood** adjusts final product size
- Transmission with belts in XPC**
- Adjustable Hardox® counter-blade** effectively control the final product size
- Skids with interchangeable Hardox® shoes and ploughshares** help the machine better penetrate the ground

**MAIN OPTIONS**

- 1 Grader blade** for compaction
- 2 Hydraulic top link** to achieve and maintain depth

MODEL	Power (HP)		PTO (rpm)	Working width (mm)	Total width (mm)	Weight (kg)	Max shredding diameter (mm)	Max working depth (mm)	No. teeth type	
	min	max							STC/3	STC/3/HD
STCH 200	180	280	1000	2080	2550	4300	500	250	52+4	
STCH 225	200	280	1000	2320	2790	4540	500	250	58+4	
STCH 250	220	280	1000	2560	3030	4780	500	250	66+4	
STCH/HD 225	200	300	1000	2320	2790	4770	500	250	/	62
STCH/HD 250	220	300	1000	2560	3030	5120	500	250	/	70

Data refers to machine as standard. The technical data in this catalog may be altered without prior notice.